

CPL

Christian Ploderer, 2003

34



226



288







Cpl mini W1.W3.W5

Christian Ploderer, 2008



W1.W3 /max 1x60W HSGST G9 

W5 /max 1x75W HSGST G9 

Struttura: alluminio cromato
o verniciato bianco opaco.
Diffusore: vetro soffiato
opalino satinato o lucido.
Protezione IP44 in pyrex satinato.


Structure: chrome or matt
white painted aluminium.
Diffuser: satin opal white
or bright white blown glass.
IP44 protection.

Befestigung: Aluminium
verchromt oder matt weiß lackiert.
Diffusor: mundgeblasenes Glas,
opal oder weiß glänzend.
Schutzklasse IP44.


Structure: aluminium
chromé ou verni blanc mat.
Diffuseur: verre soufflé
opalin blanc satiné ou brillant.
Protection IP44.

Estructura: aluminio
cromado o pintado blanco mate.
Difusor: cristal soplado opalino
blanco satinado o brillante.
Proteccion IP44.


W1



W3



W5










Cpl W1

Christian Ploderer, 2000



clear glass / max 1x150W IAA E27 
clear glass / max 1x100W IAA E27 
opal glass / max 1x100W IAA E27 
opal glass / 1x23W FBT E27 



Supporto a muro: metallo cromato o nichelato spazzolato.

Diffusore: vetro soffiato.

Wall support: chrome or brushed nickel metal.

Diffuser: blown glass.

Halterung: Metall verchromt oder Nickel gebürstet.

Diffusor: geblasenes Glas.

Support: métal chromé ou nickel brossé.

Diffuseur: verre soufflé.

Soporte: metal cromado o níquel cepillado.

Difusor: cristal soplado.



